



TOYO LED ELECTRONICS LIMITED

Room 1610, Hong Kong Plaza, 188 Connaught Road West, Hong Kong.
Tel : (852) 2540 7288 Fax : (852) 2517 1797
http://www.toyo-led.com E-mail : sales@toyo-led.com



P/N: TY-3528URPG2

3.5 * 2.8mm TOP SMD Series

◆ Features:

- 3.5mm×2.8mm SMT LED, 1.90mm thickness
- PLCC-2 package
- White package
- Suitable for all SMT assembly and solder process
- Available on tape and reel



◆ Description


The Red source color devices are made with AlGaInP on sapphire Light Emitting Diode.

The Green source color devices are made with InGaN on Green Light Emitting Diode.

◆ Application

- Optical indicator
- Indicator and backlighting in telephone and fax
- Flat backlight for LCD, switch and symbol
- Light pipe application
- General use

◆ Package Dimensions



NOTES:

1. All dimensions are in millimeter[unit];
2. Tolerance is ±0.2mm(0.008 ") especially other specified;
3. Specifications are subject to change without notice.



TOYO LED ELECTRONICS LIMITED

Room 1610, Hong Kong Plaza, 188 Connaught Road West, Hong Kong.
 Tel : (852) 2540 7288 Fax : (852) 2517 1797
 http://www.toyo-led.com E-mail : sales@toyo-led.com



P/N: TY-3528URPG2

3.5 * 2.8mm TOP SMD Series

Part No.	Emitted Color		Len's Color	Chip Material	
TY-3528URPG2	Red	Green	Water Clear	AlGaInP	InGaN

✧ Absolute Maximum Ratings(Ta=25°C)

Item	Symbol		Maximum	Unit
Power Dissipation	PD	R	60	mW
		G	95	
Continuous Forward Current	I _{Fmax}	R	30	mA
		G	25	
Peak Forward Current(1/10 Duty Cycle 0.1ms Pulse Width)	I _{FP}	R	90	mA
		G	135	
Peverse Voltage	V _R		5	V
Operating Temperature Range	T _{opr}		-40 to+85	25°C
Storage Temperature Range	T _{stg}		-40 to+85	25°C

✧ Electrical/Optical Characteristics(Ta=25°C)

Item	Symbol	Condition	Min.	Typ.	Max	Unit	
Forward Voltage	V _F	R	I _F =20mA	1.80	2.00	2.30	V
		G		3.00	3.20	3.50	
Luminous Intensity	I _V	R	I _F =20mA	300	480	700	mcd
		G		700	870	1100	
Luminous Flux	Φ	R	I _F =20mA	1.0	1.7	2.2	lm
		G		2.8	3.0	3.5	
Wavelength	λ	R	I _F =20mA	620	622	630	nm
		G		517	522	527	
Typical Correlated Color Temperature	T _c	R	I _F =20mA	--	--	--	K
		G		--	--	--	
Chromaticity Coordinates	X	I _F =20mA	--	--	--	--	
	Y	I _F =20mA	--	--	--	--	
Viewing Angle	2θ _{1/2}	I _F =20mA	--	120	--	Deg	
Capacitance	C	R	V _F =0V, f=1MHZ	--	95	--	pF
		G		--	45	--	
Reverse Current	IR	V _R =5V	--	5	10	uA	



TOYO LED ELECTRONICS LIMITED







Room 1610, Hong Kong Plaza, 188 Connaught Road West, Hong Kong.
 Tel : (852) 2540 7288 Fax : (852) 2517 1797
 http://www.toyo-led.com E-mail : sales@toyo-led.com



P/N: TY-3528URPG2

3.5 * 2.8mm TOP SMD Series

◇ Typical Electro-Optical Characteristics Curves





TOYO LED ELECTRONICS LIMITED

Room 1610, Hong Kong Plaza, 188 Connaught Road West, Hong Kong.
 Tel : (852) 2540 7288 Fax : (852) 2517 1797
 http://www.toyo-led.com E-mail : sales@toyo-led.com



P/N: TY-3528URPG2


3.5 * 2.8mm TOP SMD Series

◇ Reliability Test Items And Conditions

NO.	Item	Test Condition	Test Hr/cycle/time	Sample Q'ty	Ac/Re
1	Reflow	TEMP:260±5°C; Min.5Sec	6 min	22pcs	0/1
2	Temperature Cycle	H:+100°C 15mins To(5mins) L:-40°C 15mins	300 cycles	22pcs	0/1
3	Thermal Shock	H:+100°C 15mins To(5mins) L:-40°C 15mins	300 cycles	22pcs	0/1
4	High Temperature Storage	TEMP:+260°C	1000hrs	22pcs	0/1
5	Low Temperature Storage	TEMP:-40°C	1000hrs	22pcs	0/1
6	DC Operating Life	IF=20MA	1000hrs	22pcs	0/1
7	High Temperature	85°C	1000hrs	22pcs	0/1
8	High Humidity	85%R.H.	1000hrs	22pcs	0/1

◇ SMT Reflow Soldering Instructions

Number of reflow process shall be than 2 times and cooling
 Process to normal temperature is required between first and second
 soldering process





TOYO LED ELECTRONICS LIMITED


Room 1610, Hong Kong Plaza, 188 Connaught Road West, Hong Kong.
Tel : (852) 2540 7288 Fax : (852) 2517 1797
http://www.toyo-led.com E-mail : sales@toyo-led.com





P/N: TY-3528URPG2

3.5 * 2.8mm TOP SMD Series

❖ Recommended Soldering Pad Dimensions



❖ Tape Specification: 2,000PCS per reel



❖ Package Label

SMD LED	
PART NO: _____	QA Pass
LOT NO : _____	
Q' TY : _____	
VF : _____ IV : _____	
WL : _____ BIN: _____	Pb
DATA : _____	
TOYO LED ELECTRONICS LIMITED	
Website: http://www.toyo-led.com E-mail: sales@toyo-led.com	



TOYO LED ELECTRONICS LIMITED

Room 1610, Hong Kong Plaza, 188 Connaught Road West, Hong Kong.
Tel : (852) 2540 7288 Fax : (852) 2517 1797
http://www.toyo-led.com E-mail : sales@toyo-led.com



P/N: TY-3528URPG2

3.5 * 2.8mm TOP SMD Series

❖ Package & Shipping Instructions

