



# TOYO LED ELECTRONICS LIMITED

Room 1610, Hong Kong Plaza, 188 Connaught Road West, Hong Kong.  
Tel : (852) 2540 7288 Fax : (852) 2517 1797  
http://www.toyo-led.com E-mail : sales@toyo-led.com



## P/N: TY-5050UY1

5.0 \* 5.0mm TOP SMD Series

### ◆ Features:

- 5.0mm×5.0mm SMT LED, 1.60mm thickness
- PLCC-6 package
- White package
- Suitable for all SMT assembly and solder process
- Available on tape and reel




### ◆ Description

The Yellow source color devices are made with AlGaInP on sapphire Light Emitting Diode.

### ◆ Application

- Optical indicator
- Indicator and backlighting in telephone and fax
- Flat backlight for LCD, switch and symbol
- Light pipe application
- General use

### ◆ Package Dimensions



### NOTES:

1. All dimensions are in millimeter[unit];
2. Tolerance is ±0.2mm(0.008 ") especially other specified;
3. Specifications are subject to change without notice.



# TOYO LED ELECTRONICS LIMITED

Room 1610, Hong Kong Plaza, 188 Connaught Road West, Hong Kong.  
 Tel : (852) 2540 7288 Fax : (852) 2517 1797  
 http://www.toyo-led.com E-mail : sales@toyo-led.com



## P/N: TY-5050UY1

5.0 \* 5.0mm TOP SMD Series

Part No.	Emitted Color	Len's Color	Chip Material
TY-5050UY1	Yellow	Water clear	AllInGaP

### ✧ Absolute Maximum Ratings(Ta=25°C)

Item	Symbol	Maximum	Unit
Power Dissipation	PD	280	mW
Continuous Forward Current	I <sub>Fmax</sub>	90	mA
Peak Forward Current(1/10 Duty Cycle 0.1ms Pulse Width)	I <sub>FP</sub>	140	mA
Peverse Voltage	V <sub>R</sub>	5	V
Operating Temperature Range	T <sub>opr</sub>	-40 to+85	25°C
Storage Temperature Range	T <sub>stg</sub>	-40 to+85	25°C

### ✧ Electrical/Optical Characteristics(Ta=25°C)

Item	Symbol	Condition	Min.	Typ.	Max	Unit
Forward Voltage	V <sub>F</sub>	I <sub>F</sub> =60mA	1.9	2.2	2.4	V
Luminous Intensity	I <sub>v</sub>	I <sub>F</sub> =60mA	800	1100	1400	mcd
Luminous Flux	Φ	I <sub>F</sub> =60mA	2.9	3.7	4.5	lm
Wavelength	λ	I <sub>F</sub> =60mA	585	590	595	nm
Typical Correlated Color Temperature	T <sub>c</sub>	I <sub>F</sub> =60mA	--	--	--	K
Chromaticity Coordinates	X	I <sub>F</sub> =60mA	--	--	--	--
	Y	I <sub>F</sub> =60mA	--	--	--	--
Viewing Angle	2θ <sub>1/2</sub>	I <sub>F</sub> =60mA	--	120	--	Deg
Capacitance	C	V <sub>F</sub> =0V, f=1MHZ	--	45	--	pF
Reverse Current	I <sub>R</sub>	V <sub>R</sub> =5V	--	5	10	uA



# TOYO LED ELECTRONICS LIMITED







Room 1610, Hong Kong Plaza, 188 Connaught Road West, Hong Kong.  
Tel : (852) 2540 7288 Fax : (852) 2517 1797  
http://www.toyo-led.com E-mail : sales@toyo-led.com



## P/N: TY-5050UY1

5.0 \* 5.0mm TOP SMD Series

### ◇ Typical Electro-Optical Characteristics Curves





# TOYO LED ELECTRONICS LIMITED

Room 1610, Hong Kong Plaza, 188 Connaught Road West, Hong Kong.  
 Tel : (852) 2540 7288 Fax : (852) 2517 1797  
 http://www.toyo-led.com E-mail : sales@toyo-led.com



**P/N: TY-5050UY1**


5.0 \* 5.0mm TOP SMD Series

## ◇ Reliability Test Items And Conditions

NO.	Item	Test Condition	Test Hr/cycle/time	Sample Q'ty	Ac/Re
1	Reflow	TEMP:260±5°C; Min.5Sec	6 min	22pcs	0/1
2	Temperature Cycle	H:+100°C 15mins To(5mins) L:-40°C 15mins	300 cycles	22pcs	0/1
3	Thermal Shock	H:+100°C 15mins To(5mins) L:-40°C 15mins	300 cycles	22pcs	0/1
4	High Temperature Storage	TEMP:+260°C	1000hrs	22pcs	0/1
5	Low Temperature Storage	TEMP:-40°C	1000hrs	22pcs	0/1
6	DC Operating Life	IF=20MA	1000hrs	22pcs	0/1
7	High Temperature	85°C	1000hrs	22pcs	0/1
8	High Humidity	85%R.H.	1000hrs	22pcs	0/1

## ◇ SMT Reflow Soldering Instructions

Number of reflow process shall be than 2 times and cooling  
 Process to normal temperature is required between first and second  
 soldering process





# TOYO LED ELECTRONICS LIMITED


Room 1610, Hong Kong Plaza, 188 Connaught Road West, Hong Kong.  
Tel : (852) 2540 7288 Fax : (852) 2517 1797  
http://www.toyo-led.com E-mail : sales@toyo-led.com




**P/N: TY-5050UY1**

5.0 \* 5.0mm TOP SMD Series

### ◇ Recommended Soldering Pad Dimensions



### ◇ Tape Specification: 1,000PCS per reel



### ◇ Package Label

<b>SMD LED</b>	
PART NO: _____	QA Pass
LOT NO : _____	
Q' TY : _____	
VF : _____ IV : _____	
WL : _____ BIN: _____	Pb
DATA : _____	
TOYO LED ELECTRONICS LIMITED	
Website: <a href="http://www.toyo-led.com">http://www.toyo-led.com</a> E-mail: <a href="mailto:sales@toyo-led.com">sales@toyo-led.com</a>	



# TOYO LED ELECTRONICS LIMITED

Room 1610, Hong Kong Plaza, 188 Connaught Road West, Hong Kong.  
Tel : (852) 2540 7288 Fax : (852) 2517 1797  
http://www.toyo-led.com E-mail : sales@toyo-led.com



**P/N: TY-5050UY1**

5.0 \* 5.0mm TOP SMD Series

## ❖ Package & Shipping Instructions

