





PACKAGE DIMENSION

TY-571BL5TD50-850



Selection Guide

Part No.	Dice		Lens Color	(If=20mA)	Viewing Angle
	Raw Material	Emitted Color		TYP. (Mcd)	
TY-571BL3TD50-850	InGaN	Blue	Tiny Blue Diffused	850	50°

Absolute Maximum Ratings at T_A=25°C

Parameter	Symbol	Maximum Rating	Units
Power Dissipation	PD	120	mW
Peak Forward Current ⁴	IFP	100	mA
Forward Current	IF	30	mA
Reverse Voltage	V _R	5	V
Capacitance	C	100	pF
Operating/Storage Temperature	T _A /T _{STG}	-40°C to +85°C	
Lead Solder Temperature	T _{SOL}	260°C for 5 Seconds	

Electrical / Optical Characteristics at T_A=25°C

Parameter	Symbol	TYP.	MAX.	Units	Test Condition
Peak Wavelength	λ _{peak}	468	-	nm	I _F =20mA
Dominant Wavelength	λ _D	465	-	nm	I _F =20mA
Spectral Line Half-width	Δλ	35	-	nm	I _F =20mA
Forward Voltage	V _F	3.20	3.80	V	I _F =20mA
Reverse Current	I _R	-	1	uA	V _R =5V

Notes:

1. All dimension are in millimeter (inches);
2. Tolerance is ±0.25mm(0.01") unless otherwise specified;
3. Not recommend to solder within 3mm from the resin;
4. 1/10 Duty Cycle, 0.1ms Pulse Width.