





## PACKAGE DIMENSION

**TY-572SR2YG2W65-60**



### Selection Guide

Part No.	Dice		Lens Color	(If=20mA)	Viewing Angle
	Raw Material	Emitted Color		TYP. (Mcd)	
TY-572SR2YG2W65-60	GaAlAs	Super Bright Red	Water Clear	60	65°
	GaP	Yellow Green		50	65°

### Absolute Maximum Ratings at TA=25°C

Parameter	Symbol	Maximum Rating		Units
		SR	YG	
Power Dissipation	PD	72	65	mW
Peak Forward Current <sup>4</sup>	IFP	100	100	mA
Forward Current	IF	30	25	mA
Reverse Voltage	VR	5	5	V
Capacitance	C	95	45	pF
Operating/Storage Temperature	TA/TSTG	-40°C to +85°C		
Lead Solder Temperature	TSOL	260°C for 5 Seconds		

### Electrical / Optical Characteristics at TA=25°C

Parameter	Symbol	TYP.		MAX.		Units	Test Condition
		SR	YG	SR	YG		
Peak Wavelength	$\lambda_{peak}$	660	572	-	-	nm	IF=20mA
Dominant Wavelength	$\lambda_D$	643	568	-	-	nm	IF=20mA
Spectral Line Half-width	$\Delta\lambda$	20	30	-	-	nm	IF=20mA
Forward Voltage	VF	1.85	2.28	2.25	2.50	V	IF=20mA
Reverse Current	IR	-	-	10	10	uA	VR=5V

Notes:

1. All dimension are in millimeter (inches);
2. Tolerance is  $\pm 0.25\text{mm}(0.01")$  unless otherwise specified;
3. Not recommend to solder within 3mm from the resin;
4. 1/10 Duty Cycle, 0.1ms Pulse Width.