





## PACKAGE DIMENSION

TY-573UR5W30-1200



### Selection Guide

Part No.	Dice		Lens Color	(If=20mA)	Viewing Angle (20°)
	Raw Material	Emitted Color		TYP. (mcd)	
TY-573UR5W30-1200	AlGaInP	Ultra Bright Red	Water Clear	1200	H.H. - 30° V.V. - 80°

### Absolute Maximum Ratings at T<sub>A</sub>=25°C

Parameter	Symbol	Maximum Rating	Units
Power Dissipation	PD	78	mW
Peak Forward Current <sup>4</sup>	IFP	100	mA
Forward Current	IF	50	mA
Reverse Voltage	V <sub>R</sub>	5	V
Capacitance	C	25	pF
Operating/Storage Temperature	T <sub>A</sub> /T <sub>STG</sub>	-40°C to +85°C	
Lead Solder Temperature	T <sub>SOL</sub>	260°C for 5 Seconds	

### Electrical / Optical Characteristics at T<sub>A</sub>=25°C

Parameter	Symbol	TYP.	MAX.	Units	Test Condition
Peak Wavelength	λ <sub>peak</sub>	627	-	nm	I <sub>F</sub> =20mA
Dominant Wavelength	λ <sub>D</sub>	620	-	nm	I <sub>F</sub> =20mA
Spectral Line Half-width	Δλ	20	-	nm	I <sub>F</sub> =20mA
Forward Voltage	V <sub>F</sub>	1.90	2.25	V	I <sub>F</sub> =20mA
Reverse Current	I <sub>R</sub>	-	10	uA	V <sub>R</sub> =5V

Notes:

1. All dimension are in millimeter (inches);
2. Tolerance is ±0.25mm(0.01") unless otherwise specified;
3. Not recommend to solder within 3mm from the resin;
4. 1/10 Duty Cycle, 0.1ms Pulse Width.