



TOYO LED ELECTRONICS LIMITED

Unit 10-11, 19/F, Metro Loft, 38 Kwai Hei Street, Kwai Chung, N.T., Hong Kong.

Tel : (852) 2540 7288

http://www.toyo-led.com

Fax : (852) 2517 1797

E-mail : sales@toyo-led.com



CODE:WH1

CHARACTERS

Chip Material: InGaN Blue LED Chip

ABSOLUTE MAXIMUM RATINGS (Ta = 25°C)

PARAMETER	SYMBOL	MAXIMUM RATING	UNIT
Power Dissipation	P _D	90	mW
Peak Forward Current (1/10 Duty Cycle, 0.1 ms Pulse Width)	I _{PEAK}	100	mA
DC Forward Current	I _F	25	mA
Reverse Voltage	V _R	5	V
Electrostatic discharge	ESD	1000	V
Operating Temperature Range	(T _{opr}) / T _{stg}	-40°C to +85°C	
Storage Temperature Range	T _{opr} / (T _{stg})	-40°C to +100°C	

ELECTRICAL OPTICAL CHARACTER AND CURVES (Ta = 25°C)

PARAMETER	SYMBOL	MIN	TYP	MAX	UNIT	TEST CONDITION (Per Chip)
Forward Voltage	V _F	-	3.0	3.6	V	I _F = 20mA
Luminous Intensity	I _v	60	80	-	mcd	I _F = 20mA
Color Temperature	CCT	-	5000	-	K	I _F = 20mA
Spectral Line Coordinates	Δλ	-	30	-	nm	I _F = 20mA
Reverse Current	I _R	-	-	10	uA	V _R = 5V

Note:

1. The white light of an LED generated by a blue source exciting the yellow phosphor
2. Luminous intensity tolerance is ±15%;



TOYO LED ELECTRONICS LIMITED

Unit 10-11, 19/F, Metro Loft, 38 Kwai Hei Street, Kwai Chung, N.T., Hong Kong.

Tel : (852) 2540 7288

<http://www.toyo-led.com>

Fax : (852) 2517 1797

E-mail : sales@toyo-led.com



CODE:WH1

Typical Electro-Optical Characteristic Curve

FIG. 1 Forward Current Vs. Forward Voltage




FIG. 2 Relative Intensity Vs. Forward Current




FIG. 3 Forward Voltage Vs. Temperature




FIG. 4 Relative Intensity Vs. Temperature




FIG. 5 Relative Intensity Vs. Wavelength

