

DYO LED ELECTRONICS LIMITED

 Unit 10-11, 19/F, Metro Loft, 38 KwaiHei Street, Kwai Chung, N.T., Hong Kong

 Tel: (852) 2540 7288
 Fax: (852) 2517 1797

 http://www.toyo-led.com
 E-mail: sales@toyo-led.com



P/N:TY-Y0805PG1(0.80)

0805Package 2.0*1.25mmSurface Mount LEDs Series

SPECIFICATION FOR CUSTOMER APPROVAL

P/N: TY-Y0805PG1(0.80)

DATE : May 27, 2025

PREPARED BY : STEVEN

CONFIRMED BY :

PLEASE CONFIRM & SIGN BACK THIS SHEET TO US

CUSTOMER:

APPROVAL BY:

(COMPANY CHOP)

(SIGNATURE)





Unit 10-11, 19/F, Metro Loft, 38 KwaiHei Street, Kwai Chung, N.T., Hong Kong Tel: (852) 2540 7288 Fax: (852) 2517 1797 http://www.toyo-led.com E-mail : sales@toyo-led.com



P/N:TY-Y0805PG1(0.80)

0805Package 2.0*1.25mmSurface Mount LEDs Series

Features: \geq

- 2.0*1.25*0.8mm ∻
- ∻ Mono-color type
- Soldering methods :All SMT assembly methods ∻
- ∻ Comply ROHS standard

Description \geq

The Green source color devices are made with InGaN on sapphire Light Emitting Diode.

Application \succ

- Optical indicator \geq
- Indicator and backlighting in telephone and fax \triangleright
- Flat backlight for LCD,switch and symbol \triangleright
- Light pipe application \triangleright
- General use \triangleright

Package Dimensions



3. Specifications are subject to change without notice.

NOTES:

1. 2.





0805Package 2.0*1.25mmSurface Mount LEDs Series

Part No.	Emitted Color	Lens Color	Chip Material
TY-Y0805PG1(0.80)	Green	Water Clear	InGaN

➤ Absolute Maximum Ratings(Ta=25°C)

Item	Symbol	Maximum	Unit
Power Dissipation	PD	75	mW
Continuous Forward Current	I _{Fmax}	25	mA
Peak Forward Current(1/10 Duty Cycle 0.1ms Pulse Width)	I _{FP}	60	mA
Reverse Voltage	V _R	5	V
Electrostatic Discharge	ESD	1000	V
Operating TemperatureRange	T _{opr}	-40 to+85	°C
Storage TemperatureRange	T _{stg}	-40 to+85	°C
Lead Solder Temperature	Tsol	260°C for 3 seconds	

> Electrical/Optical Characteristics(Ta=25°C)

Item	Symbol	Condition	Min.	Тур.	Max	Unit
Forward Voltage	V _F	I _F =10mA	2.6	3.0	3.2	V
Luminous Intensity	Iv	I _F =10mA	400	600		mcd
Wavelength	λd	I _F =10mA	515	525	535	nm
Viewing Angle	$2\theta_{1/2}$	I _F =10mA		120		Deg
Reverse Current	IR	$V_R = 5V$			10	uA









 Unit 10-11, 19/F, Metro Loft, 38 KwaiHei Street, Kwai Chung, N.T., Hong Kong

 Tel: (852) 2540 7288
 Fax: (852) 2517 1797

 http://www.toyo-led.com
 E-mail: sales@toyo-led.com



P/N:TY-Y0805PG1(0.80)

0805Package 2.0*1.25mmSurface Mount LEDs Series

NO.	Item	Test Condition	Test Hr/cycle/time	Sample Q'ty	Ac/Re
1	Reflow	TEMP:260±5℃; Min.5Sec	6 min	22pcs	0/1
2	Temperature Cycle	H:+100°C 15mins To(5mins) L:-40°C 15mins	100 cycles	22pcs	0/1
3	Thermal Shock	H:+100°C 15mins To(5mins) L:-40°C 15mins	500 cycles	22pcs	0/1
4	High Temperature Storage	TEMP:+260℃	1000hrs	22pcs	0/1
5	Low Temperature Storage	TEMP:-40°C	1000hrs	22pcs	0/1
6	DC Operating Life	IF=20MA	1000hrs	22pcs	0/1
7	High Temperature	85°C	1000hrs	22pcs	0/1
8	High Humidity	85%R.H.	1000hrs	22pcs	0/1

> Reliability Test Items And Conditions

> SMT Reflow Soldering Instructions

Reflow soldering			Hand welding		
	Lead Solder	Lead-free Solder	Temperature	350° C Max.	
Pre-heat	140 ~ 160° C	180 ~ 200° C	Soldoning time		
Pre-heat time	120 sec. Max.	120 sec. Max.	Soldering time	3 sec. max. (onetime only)	
Peak temperature	230° C Max.	260° C Max.			
Soldering time	10 sec. Max.	10 sec. Max.			
Condition	Refer to the	Refer to the			
	picture below	picture below			













TOYO LED ELECTRONICS LIMITED

 Unit 10-11, 19/F, Metro Loft, 38 KwaiHei Street, Kwai Chung, N.T., Hong Kong

 Tel: (852) 2540 7288
 Fax: (852) 2517 1797

 http://www.toyo-led.com
 E-mail: sales@toyo-led.com



P/N:TY-Y0805PG1(0.80)

0805Package 2.0*1.25mmSurface Mount LEDs Series

Handling Precautions

Compare to epoxy encapsulant that is hard and brittle, silicone is softer and flexible. Although its characteristic

significantly Orangeuces thermal stress, it is more susceptible to damage by external mechanical force.

As a result, special handling precautions need to be observed during assembly using silicone encapsulated LED products. Failure to comply might lead to damage and premature failure of the LED.

1. Handle the component along the side surface by using forceps or appropriate tools; do not directly touch or Handlethe silicone lens surface, it may damage the internal circuitry.



2. The outer diameter of the SMD pickup nozzle should not exceed the size of the LED to preve air leaks. The inner diameter of the nozzle should be as large as possible. A pliable material is suggested for the nozzle tip to avoid scratching or damaging the LED surface during pickup. The dimensions of the component must be accurately programmed in the pick-and-place machine to insure precise pickup and avoid damage during production.

3. Do not stack together assembled PCBs containing environment, PH<7

4.Not suitable to operate in acidic

LEDs. Impact may scratch the silicone lens or damage the internal circuitry





5. LED operating environment and sulfur element composition cannot be over 100PPM in the LED mating usage material.

6. When we need to use external glue for LED application products, please make sure that the external glue matches the

LED packaging glue. Additionally ,as most of LED packaging glue is silica gel, and it has strong Oxygen permeability as well as strong moisture permeability; in order to prevent external material from getting into the inside of LED, which

may cause the malfunction of LED, the single content of Bromine element is required to be less than 900PPM,the



0805Package 2.0*1.25mmSurface Mount LEDs Series

single

content of Chlorine element is required to be less than 900PPM, the total content of Bromine element and Chlorine

element in the external glue of the application products is required to be less than 1500PPM



OYO LED ELECTRONICS LIMITED

 Unit 10-11, 19/F, Metro Loft, 38 KwaiHei Street, Kwai Chung, N.T., Hong Kong

 Tel : (852) 2540 7288
 Fax : (852) 2517 1797

 http://www.toyo-led.com
 E-mail : sales@toyo-led.com



P/N:TY-Y0805PG1(0.80)

0805Package 2.0*1.25mmSurface Mount LEDs Series

ESD (Electrostatic Discharge)

Static Electricity or power surge will damage the LED. Use of a conductive wrist band or anti-electrostatic glove is recommended when handing these LED. All devices, equipment and machinery must be properly grounded.

Notes for designing

Care must be taken to provide the current limiting resistor in the circuit so as to drive the TOYO LEDs within the rated figures. Also, caution should be taken not to overload TOYO LEDs with instantaneous voltage at the turning ON and OFF of the circuit.

When using the pulse drive care must be taken to keep the average current within the rated figures. Also, the circuit should be designed so as be subjected to reverse voltage when turning off the TOYO LEDs.

Storage

1. We recommend the reflow temperature 230 ± 5 °C $\,$. The maximum soldering temperature should be limited to 240 °C $\,$ for 10s (max).

2. SMD products are easily moisturized. Before soldering the unpacked SMD, de-moisturize process under $65\pm5^{\circ}$ C /24 hours is recommended. It could effectively prevent the defects caused by rapid expend of hydro particles in the plastic under heat;

3. All unpacked and de-moisturized SMD should be used up within 168 hours. Otherwise, you need to de-moisturize them under $65\pm5^{\circ}$ C /24 hours again;

4. During reflow soldering, tin paste high in hydro or with sulfide cannot be used; Also, avoid using thinner to remained tin paste for fear that moistures penetrate to the base of the SMD and cause defects.

5. SMD storage conditions: 5-30 $^\circ\!\!{\rm C}\,$, humidity: 60% MAX

6. Product is not recommended to work in high temperature and high humidity environment, will affect the life of the product

7. During manual welding, the welding temperature should be controlled at $350 \circ c/3$ seconds to avoid direct contact with the product colloid at the high temperature of luotie head, so as to prevent defective dead lamps caused by high temperature during welding

8. The number of reflow welding of the product is 1, and the repeated reflow will cause the product dead lamp to be defective

9. Moisture sensitivity level: 3



TOYO LED ELECTRONICS LIMITED

 Unit 10-11, 19/F, Metro Loft, 38 KwaiHei Street, Kwai Chung, N.T., Hong Kong

 Tel: (852) 2540 7288
 Fax: (852) 2517 1797

 http://www.toyo-led.com
 E-mail: sales@toyo-led.com



P/N:TY-Y0805PG1(0.80)

REVISION HISTORY				
DATE	REVISION CONTENTS	VERSION		
2025-03-13	Initial release	А		